

ALLEGAN COUNTY ROAD COMMISSION

SPECIFICATIONS FOR TANDEM AXLE DUMP TRUCK

The following is a list of Minimum Acceptable Requirements for trucks that are to be bid under this proposal. All blank spaces listing options or dimensions are to be filled in. If it is impossible to provide certain items that are required list all exceptions and options below. All bids are to include delivery of units to the Road Commission.

Truck GVWR Minimum 64,000 lbs. Truck GVWR is _____

1. Engine – (Shall be 2020 emissions compliant, Detroit or Cummins) 450 HP, 1650 lb-ft torque minimum.

Engine Bid Make _____, Model _____ HP _____

Torque _____, @ _____ RPM

2. Engine Requirements-

- (a) Automatic shutdown for low oil pressure and coolant
- (b) Replaceable filters
- (c) Front crankshaft adapter for P.T.O. – 1350 adapter flange
- (d) Engine to be retro-fitted for overhead fuel tank system
- (e) Engine and after treatment system warranty, 7 yr, 250,000 mile, 100% parts and labor
- (f) Engine software cables, adapters and paper manuals
- (g) Mechanic training for updates and changes

NOTE: P.T.O. shaft & pump to be installed by fabricator.

3. Radiator & Grill - Heavy duty radiator to accommodate front mounted P.T.O. pump, shaft, and joint assembly.

NOTE: Hole in radiator and grill is unacceptable.

4. Allison Automatic Transmission

- (a) 6-speed model 4500 RDS with synthetic Allison fluid
- (b) Push button shift control
- (c) Low oil level sensor
- (d) 5-yr, 200,000 mile extended warranty
- (e) Transmission ECU mounted inside the cab (performed by dealer, all factory connections with sealer, no splices)

5. Drive Line – 1810 heavy duty drive line with two-section shaft with center bearing and half round u joints.

6. Rear Axle - Rockwell RT-46-160, driver operated differential lock in both rear axles and magnetic drain plugs.
Gear Ratio 5.63 for a road speed not to exceed 60 M.P.H. at 1900 RPM.
Startability factor not to be less the 38. Startability factor is _____ .

7. Rear Suspension – 46,000 lb Nuway ADZ-246 air ride height control valve, one valve per side shall control both axles, right side linkage shall be adjustable.

8. Front Axle – Meritor, minimum capacity 20,000 lbs. Set back type set at approximately 33 inches in back of grill. (see wheel base dimensions, section 12)
(a) Vented hub caps

9. Front Springs - Taper-leaf type Yes _____ No _____ 10,000 lbs. each spring.
(a) Greaseable shackle pins, minimum diameter - 1 inch.

10. Power Steering - Hydraulic Assisted, TRW gears
Turning Radius Degree _____, outer circumference _____ feet

11. Air Brakes - Spring-set parking brake with warning light & buzzer.
- Compressor shall be a Bendix BA-921 or equal.
 - Front Brakes: 16 1/2 X 6" Rockwell TQ, S-Cam with dust shields and Haldex automatic slack adjuster.
 - Rear Brakes: 16 1/2 X 7" Rockwell TQ, S-Cam with dust shields and Haldex automatic slack adjuster.
 - Haldex Gold Seal Brake Chambers.
 - Heated air dryer Wabco spin on type
 - Wabco ABS
 - Air tanks mounted on outside of frame rails
12. Frame – RBM = 3,200,000 / Strength = 120,000 PSI minimum
 Single Channel _____ Double Channel _____
 If Single Channel
 Channel dimensions _____ x _____
 R.B.M. _____ Strength _____ Section Modulus _____
 If Double Channel Frame
 Main channel dimensions _____ x _____
 Secondary channel dimensions _____ x _____
 R.B.M. _____ Strength _____ Section Modulus _____
 Frame to have all seams sealed
- Frame to have one (1) cross member behind rear axle
 - Frame to have two (2) cross members in cab to axle section minimum
 - Frame to have one (1) cross member at rear cab support and one (1) cross member at front of motor.
 - Wheelbase – 211 inches minimum
 - Cab-to-axle - 138 inches minimum
 - Set back front axle
 - AF 65" minimum. (center of drive axles to rear of frame)
 - No holes shall be placed in frame that are not necessary for assembly or attachment.
 - Frame to extend 20" ahead of grill (bolt on frame extensions are NOT acceptable).
 - All frame mounted equipment to have minimum 24" ground clearance.
 - Top of frame shall be straight from front to rear.
13. Shock Absorbers – Six shocks required, two per axle
14. Tires, Hubs, and Wheels –
- Front tires shall be size of 315-80R-22.5
 - Front wheels shall be heavy duty steel ten (10) hole disc hub piloted
 - Dual rear tires shall be size of 12R-22.5
 - Rear wheels shall be heavy duty ten (10) hole disc hub piloted unimount
15. Electrical System ** multi-plex wiring outside of cab is not acceptable **
- Multiplex Chassis Yes _____ No _____
 Multiplex Cab Yes _____ No _____
- 12 volt, negative ground
 - 160 AMP heavy duty Delco alternator
 - Four (4) batteries minimum 2500 CCA, standard group 31
 - Batteries mounted externally on truck
 - 7 way round trailer plug and wiring to rear cross member
 - Twist tube harness coverings where applicable
16. Gauges (direct reading type) - (a) Oil pressure (b) Water temperature (c) Ammeter or Voltmeter (d) Air pressure, (e) Dash mounted air filter restriction gauge, (f) Tachometer, (g) Fuel gauge and (h) Engine hour-meter.
17. Warning lights and/or buzzers for safety - (a) for low air pressure, (b) engine overheating, (c) low oil pressure, (d) back-up alarm

18. Truck Cab
 - (a) Steel conventional cab. BBC is _____
 - (b) Cab to be corrosion and rust protected between inner and outer walls
 - (c) Air ride cab
 - (d) Key code D610
 - (e) Fiberglass sun visor
 - (f) Rear cab glass to be safety coated
 - (g) Tool box mounted under right step

19. Cab Insulation - Complete insulation package to include floor, roof, back wall, firewall and doors.

20. Tinted Windshield

21. Exhaust System
 - (a) Vertical after treatment system with vertical tailpipe mounted behind right rear corner of cab.
 - (b) After treatment control valve mounted inside the cab (performed by dealer, all factory connections with sealer, no splices)

22. Cab- Air conditioning, heater with shut off valve, cruise control, power windows, tilt wheel, Radio: AM/FM/CD/USB with blue tooth connect, spotlight on left side, heated west coast type mirrors with double brackets, heated spot mirrors, 12-V power point, marker lights, four extra ignition controlled switches, snowplow headlight prep package, air ride cab, grab handles both sides, left side roof mounted dual air horns, engine fan override switch, electric intermittent wipers, stainless cab skirts and single cup holder.

- Left side air cleaner YES _____ NO _____, must be capable of drawing inside or outside air.

23. Front Bumper - Not required

24. Driver's Seat - National 2000, Cloth Mid Back Air Suspension with arm rests

25. Passenger Seat - Standard cloth seat, tool box under seat.

26. Fuel Tank – 50 gallon tank for transporting truck only.

27. Paint Color - Red, Paint top of truck hood flat black

28. Air Tank and Exhaust Pipe - to be mounted no lower than bottom of frame (24" minimum ground clearance)

29. Parts Books, Parts CD Rom, and shop repair manuals must be furnished before final payment is made.

30. Bidders - Order to manufacturer to be checked and signed by Allegan County Road Commission before final construction order is submitted.

EXCEPTIONS:

OPTIONS:

Tire size noted above, make options to be listed here, either Good Year G289 and G622 or Michelin XZUS and XND

Factory labels on extra dash switches: front strobes, rear strobes, blade light, spreader light

Necessary Dimensions To Be Provided by Bidder

1. Distance between seats _____ inches
2. Length of hood ahead of "doghouse" or fire wall _____ inches
3. Length and width of "doghouse" in cab _____ inches _____ inches
4. Distance from back of cab to drive wheel base _____ inches
5. Distance of DEF tank from drive wheel base _____ inches
6. Distance from frame bottom to ground _____ inches

WARRANTY

<u>Component</u>	<u>Parts & Labor Coverage</u>	<u>Miles</u>	<u>Years</u>
ENGINE	100% Parts & Labor	250,000	7
ALLISON TRANSMISSION	100% Parts & Labor	200,000	OR 5
TOTAL VEHICLE	_____	_____	_____
DRIVETRAIN	_____	_____	_____
FRAME	_____	_____	_____
CAB CORROSION	_____	_____	_____
CAB STRUCTURE	_____	_____	_____
RADIATOR & COOLING SYSTEM	_____	_____	_____
EXHAUST & AFTERTREATMENT SYSTEMS	_____	_____	_____

The Allegan County Road Commission reserves the right to request any specification or component measurements

The Allegan County Road Commission reserves the right to request any specification reviews with the county, manufacturer and finishing fabricators